



经纬纺织机械股份有限公司榆次分公司
JINGWEI TEXTILE MACHINERY CO.,LTD.YUCI BRANCH

JW-PROTTI PV2P/PV3P型电脑横编机 FLAT KNITTING MACHINES (FLEX)





PV2P: 机号 E4-5-6-7-8-10-12-14-16-18

Gauges PV2P: E4-5-6-7-8-10-12-14-16-18

PV2P多针距: 机号 E5-E7-E12-E14

Gauges PV2P FLEX: E5-E7-E12-E14

双系统 No. of system 2

PV3P: 机号 E4-5-6-7-8-10-12-14-16/E2.5-3-3.5

Gauges PV3P: E4-5-6-7-8-10-12-14-16/E2.5-3-3.5

PV3P多针距: 机号 E5-E7-E12-E14

Gauges PV3P FLEX: E5-E7-E12-E14

三系统 No. of system 3

该系列是单机头双系统或三系统电脑横机，分级选针器，电子编程，用于生产提花、嵌花、结构组织及成型织物，可实现变针距编织。

It is a series of flat knitting machines fitted with 2 or 3 systems and single carriage, with needle by needle selection and electronic programming, for the production of jacquard, intarsia, structured and shaped knitwear with the possibility to knit different gauges on the same fabric.



	PV2P	PV3P	PV3P (GROSS gauge)
机头/系统数量 N° of carriages/system	1/2	1/3	1/3
编织系统 Knitting systems	2	3	3
分级选针器 Needle by needle selection with n° of selection groups	16	24	12
长度 Length cm/inch	130/52"	130/52"	130/52"
机号 Gauges	from 4 to 18	from 4 to 16	2,5 - 3 - 3,5
多针距 Flexible gauge (FLEX)	5 - 10 - 12 - 14	5 - 10 - 12 - 14	-
可更换天齿片 Interchangeable jack	●	●	●
沉入式织针 Sinkable needles	●	●	●
全沉降系统 Full sinker system	●	●	●
后针床横移, 程序控制 Programmable rear needle bed racking max.	4"	4"	4"
前针床翻转 Rotating front needle-bed	●	●	●
编织与翻针同步 Combined knitting and stitch transfer	●	●	●
自由翻针 Simultaneous double stitch transfer independently from carriage direction	●	●	●
三种编织 (成圈、集圈、浮线) 3 technical selections for knitting (knit, tuck, miss)	●	●	●
长短线圈可选 2 technical selections for stitch length (long and short stitches)	●	●	-
动态密度 Dynamic variation of stitch length	●	●	●
分针与编织/翻针同步 Split device integrated in knitting/transfer system	●	●	-
沉降片 (压、半压、不压) Sinker system with two positions of action + out of action front/rear	●	●	●
纱嘴导轨 Yarn carrier guide bars	4	4	4
纱嘴标配 Yarn carriers in standard equipment	10	10	9
上张力臂, 双重检测节点 Upper tension arms with knots double check	12	18	18
两侧张力臂 Lateral tension arms for each side	8	8	8
左右侧纱夹纱剪 Blocking and yarn cutting device on right and left side	●	●	●
磁性锥形纱管座 Magnetic cone holder	12	18	18
积极喂纱装置 (右/左) Lateral loading device on right/left side	●/※	●/※	●/※
主牵拉辊, 程序控制 Programmable main take down roller	●	●	●
辅助上牵拉辊 Additional upper take down roller	●	●	●
起底板 Set up comb with compressed air	●	●	●
倒卷或落片自停 Automatic stop motion when fabric rolls up and/or falls down	●	●	●
可变动程 Variable stroke	●	●	●
最大编织速度 Max knitting speed m/sec.	1,3	1,3	1,1
清洁系统 Suction and blower system	●	●	●
润滑系统 Oiling system device	●	●	●
滑动透明机头罩壳 Sliding transparent carriage protections	●	●	●
启动/停车操纵杆 Start and stop bar	●	●	●
设计生产制造符合CE规则 Designed, built and marked - CE rules	●	●	●
针床照明 Needle beds lighting	●	●	●
指示灯 Lighting signals	●	●	●
报警 Acoustic device when machine stops	●	●	●
微处理器, RAM内存 Multiprocessor, RAM memory	●	●	●
键盘 Alphanumeric keyboard	●	●	●
自检程序 Autodiagnosis Program	●	●	●
LCD显示 Display LCD, 800X600	●	●	●
软盘或USB Floppy disk 1.44 Mb and USB Pen Drive	●	●	●
硬盘 Hard disk 128MB	●	●	●
多语言菜单 Menu system in different languages	●	●	●
机器长度 Length of machine in mm.	2,894	2,894	3,361
机器宽度 Width machine in mm.	918	918	918
机器高度 Height of machine in mm.	1,430	1,430	1,430
包装箱长度 Length of crate in mm.	3,100	3,100	3,500
包装箱宽度 Width of crate in mm.	1,100	1,100	1,100
包装箱高度 Height of crate in mm.	1,915	1,915	1,915
毛重/净重 Weight of machine in kg net/gross	1.250/1.620	1.350/1.720	1.540/1.910

● 标配 OF SERIES ※ 选配 ONREQUEST - 不能配 NOTAVAILABLE



经纬纺织机械股份有限公司榆次分公司
JINGWEI TEXTILE MACHINERY CO.,LTD.YUCI BRANCH

地 址：山西省晋中市榆次区经纬南路1号

邮 编：030601

电 话：0354 - 2492875 2492877

传 真：0354 - 2425604

网 址：www.jwyc.com

电子信箱：jwfjb@jwyc.com

Add: No.1 ,Jingwei South Road.Yuci,Shanxi,P.R.China

Zip code: 030601

Tel: +86 354 2492584 2492585

Fax: +86 354 2426884

Http: www.jwyc.com

E-Mail: jwgmb@jwyc.com

产品规格与外观可能有变更，恕不预先通知

The specifications of the machine are subject to change without prior notice.