



经纬纺织机械股份有限公司榆次分公司
JINGWEI TEXTILE MACHINERY CO.,LTD.YUCI BRANCH

JW-PROTTI PV91/PV4型电脑横编机 FLAT KNITTING MACHINES





PV91/PV91X : 机号 E4-5-6-7-8-10-12-14

Gauges PV91/PV91X: E4-5-6-7-8-10-12-14

双系统 No. of system 2

PV91X3 : 机号 E4-5-6-7-8-10-12-14

Gauges PV91X3: E4-5-6-7-8-10-12-14

三系统 No. of system 3

PV4: 机号 E4-5-6-7-8-10-12-14

Gauges PV4: E4-5-6-7-8-10-12-14

四系统 No. of system: 4 (2+2)

该系列是应用广泛的多机头双系统、三系统或四系统电脑横机，分级选针器，电子编程，针床长度可达240（96”），用于生产提花、嵌花、结构组织及成型织物。

It is a series of highly versatile multi-carriage modular flat knitting machines fitted with 2-3-4 systems with needle by needle selection and the electronic programming with needle bed of cm 240 (96”) for the production of jacquard, intarsia, structured and shaped knitwear.



	PV91	PV91X	PV91X3	PV4
机头/系统数量 N° of carriages/systems	2/1	2/1	3/1	2/2
编织系统 Knitting systems	2	2	3	4
分级选针器 Needle by needle selection with N° of selection groups	16	16	24	32
针床长度 Needle bed length cm/inch	240/96*	240/96*	240/96*	240/96*
机号 Gauges	from 4 to 14	from 4 to 14	from 4 to 14	from 4 to 14
可更换天齿片 Interchangeable jacks	●	●	●	●
沉入式织针 Sinkable needles	●	●	●	●
机头幅宽 Working width with tandem cam carriages cm/inch.	115/46*	115/46*	两个衣片two fabrics 115/46* 三个衣片three fabrics 75/30*	
沉降片（前/后） Full sinker system front/rear	●	●	●	●
后针床横移，编程控制 Programmable rear needle bed racking max	4*	4*	4*	4*
前针床翻转 Rotating front needle-bed	●	●	●	●
编织与翻针同步 Combined knitting and stitch transfer	●	●	●	●
自由翻针 Simultaneous double stitch transfer independently from carriage direction	●	●	●	●
三种编织技术（成圈、集圈、浮线） 3 technical selections for knitting (knit, tuck, miss)	●	●	●	●
两种线圈长度 2 technical selection for stitch length	-	●	●	●
动态密度 Dynamic variation of stitch length	●	●	●	●
分针与编织/翻针同步 Split device integrated in knitting/transfer system	●	●	●	●
沉降片（压、半压、不压） Sinkers System with two positions of action and out of action front/rear	-	●	●	●
纱嘴导轨 Yarn carriers guide bars	4	4	4	4
标配纱嘴 Yarn carries in standard equipment	8	8	12	16
上张力臂，双重检测节点 Upper tension arms with knot double check	12	12	18	24
两侧张力臂 Lateral tension arms for each side	8	8	12	12
磁性锥形纱管座 Magnetic cone holder	12	12	18	24
积极喂纱装置 左/右 Yarn loading device left/right	●	●	●	●
主牵拉辊，编程控制 Programmable Main take down roller	●	●	●	●
辅助上牵拉辊 Additional Upper take down roller	-	●	●	●
倒卷自停 Automatic stop motion when fabric rolls up	●	●	●	●
落片自停 Automatic stop motion when fabric falls down	●	●	●	●
可变动程 Variable stroke	●	●	●	●
最大编织速度 Max knitting speed m/sec	1.3	1.3	1.3	1.3
清洁系统 Suction and blower system	*	●	●	●
润滑系统 Oiling system device	●	●	●	●
滑动透明机头护罩 Sliding transparent carriage protections	●	●	●	●
启动/停车操纵杆 Start and stop bar	●	●	●	●
设计生产制造符合CE规则 Designed, built and marked - in compliance to CE rules	●	●	●	●
针床照明 Needle bed lighting	●	●	●	●
指示灯 Lighting signals	●	●	●	●
报警 Acoustic warning	●	●	●	●
微处理器，RAM内存 Multiprocessor, RAM memory	●	●	●	●
键盘 Keyboard control	●	●	●	●
自检 Auto diagnosis Program	●	●	●	●
LCD显示 Display LCD	●	●	●	●
软盘或USB Floppy disk 1.44 Mb and USB Pen Drive	●	●	●	●
硬盘 Hard disk 128 Mb	●	●	●	●
多语言菜单 Menu system in different languages	●	●	●	●
机器长度 Length of machine in mm.	4.390/4.463	4.390/4.463	4.390/4.463	4.390/4.463
机器宽度 Width machine in mm.	918/1.072	918/1.072	918/1.072	918/1.072
机器高度 Height of machine in mm.	1.373/2.081	1.373/2.081	1.373/2.081	1.373/2.081
包装箱长度 Length of crate in mm.	4,600	4,600	4,600	4,600
包装箱宽度 Width of crate in mm.	1,158	1,158	1,158	1,158
包装箱高度 Height of crate in mm.	1,915	1,915	1,915	1,915
毛重/净重 Weight of machine in Kg net/gross	1810/2320	1860/2370	1900/2410	1880/2390

● 标配 OF SERIES - 不能配 NOTAVAILABLE *ON REQUEST选配

经纬纺织机械股份有限公司榆次分公司
JINGWEI TEXTILE MACHINERY CO.,LTD.YUCI BRANCH

地 址：山西省晋中市榆次区经纬南路1号

邮 编：030601

电 话：0354 - 2492875 2492877

传 真：0354 - 2425604

网 址：www.jwyc.com

电子信箱：jwfjb@jwyc.com

Add: No.1 ,Jingwei South Road.Yuci,Shanxi,P.R.China

Zip code: 030601

Tel: +86 354 2492584 2492585

Fax: +86 354 2426884

Http: www.jwyc.com

E-Mail: jwgmb@jwyc.com

产品规格与外观可能有变更，恕不预先通知

The specifications of the machine are subject to change without prior notice.